

G 500/G 1000 Standard Equipment

- ✓ Single-phase 230V/50Hz electric motor
- ✓ IP67 plug
- ✓ Frame with 4 steel wheels
- ✓ Upper limit safety device
- ✓ Direct control with 3-pushbutton IP65 1.5-m pendant control
- ✓ Positioning brake
- ✓ Self-braking motor with magnetic device

Applications G 500/G 1000

Thanks to their sturdy structure and powerful motor, G 500 and G 1000 are particularly suitable for heavy duty use on site.

220V/60Hz SPH

MOTOR AVAILABLE

✓ G 500 ✓ G 1000

ELECTRIC MOTOR
SINGLE-PHASE



G 500



G 1000

Hoists

		SINGLE-PHASE	SINGLE-PHASE
		G 500	G 1000*
Maximum capacity	kg	500	1000
Av. full load lifting speed	m/min	17	8.5
Max. working height	m	42	21
Ø wire rope	mm	6	6
Rope length	m	43	43
Motor power rate	kW	1.5 (230V/50Hz)	1.5 (230V/50Hz)
Motor speed	rpm	1300	1320
Running current	A	12	14
Machine weight	kg	71	75
SPL in operator's position	dB(A)	<72	<72
Dimensions w/l/h	mm	382/800/410	382/800/410
Packing dimensions w/l/h	mm	400/820/440	400/820/440

* AVAILABLE ONLY FOR NON-EU COUNTRIES